

Syntactic Annotation Service Contract Description v0.8 - BDOC

Contract:

Unknown macro: {multi-excerpt} Syntactic Annotation

- Brief description
 - Version
 - Overview and Definitions
 - Assumptions
 - References
 - Known Issues
- ROA Layer API
 - Base URLs
 - Schema
 - Annotation Format
 - List Export Formats
 - List Import Formats
 - Format Options
 - Annotation Repository
 - List Annotation Repository instances
 - List an Annotation Repository
 - Text Repository
 - List Text Repository instances
 - List a specific Text Repository
 - Annotation
 - Request a specific annotation or set of annotations
 - Request an annotation or set of annotations matching certain criteria
 - Annotation Template (Document)
 - Create an annotation template for a specific document.
 - Annotation Template (Text)
 - Create an annotation template for supplied text
- SOA Layer API
- Notifications
- Tests

Brief description

Version

This page describes the Syntactic Annotation Service API, v. 1.1.0.

To discover the version and other metadata about deployed service code that fulfills this API, please utilize the [Service Catalog Service - BDOC](#).

Overview and Definitions

The Syntactic Annotation Service 1.1.0 Release provides a standard API via RESTful HTTP and OSGI Service interfaces for requesting (a) syntactic annotations from supported annotation repositories and (b) templates for creation of syntactic annotations of passages and texts. It is currently configured with access to the Alpheios repository of the Perseus Greek and Latin treebank annotations. It can also retrieve text for annotation template creation from any CTS-API compliant repository, and can be easily configured to access other annotation and text repositories which provide HTTP based RESTful interfaces. The Syntactic Annotation service also supports plugins of [PepperModules](#) for converting between annotation formats. The Release 1.1.0 interface supports the Perseus import format and Perseus and PAULA export formats.

For a full description, visit the [Syntactic Annotation Service Description and Assumptions](#) page of Project Bamboo's development wiki.

Assumptions

None.

References

- Entity Diagrams
- Scholarly Services - Linguistic+Analysis

Known Issues

- **BSPSVC-83** Cannot configure which TEI tags to ignore when tokenizing text to create annotation templates.

ROA Layer API

RESTful service methods performing Create and List functions over Annotations, Annotation Repositories, Formats and Text Repositories.

Base URLs

Currently available instances of the Bamboo Services Platform are **INSECURE**, are operated with **NO EXPLICIT SLA**, and should be considered **STATELESS**: that is, data may be wiped from persistent stores at any time.

A secure instances of the BSP, with URLs that do not require explicit inclusion of a port number, and for which data will be preserved on future upgrades is anticipated in *Fall 2012*.

Currently available base URLs:

- <http://services-qa.projectbamboo.org>

To receive notices about maintenance, down-time, and other issues about instances of the Bamboo Services Platform you may subscribe to bsp-bulletins@lists.projectbamboo.org. You may [unsubscribe here](#).

Schema

- AnnotationRepositoryListRepresentation schema
- TextRepositoryListRepresentation schema
- AnnotationFormatListRepresentation schema

Annotation Format

A format available for ingestion and serialization of annotation bodies. There are two sub-categories of formats: import and export. Import formats are those formats in which the service is able ingest annotations, and export formats are those formats to which the service is able to serialize annotations. Annotations may be converted from one format to another by supplying a format for export which differs from the annotations' import format.

List Export Formats

Lists the set of available export formats for annotations.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/format/export HTTP/1.1
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an AnnotationFormatListRepresentation schema XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
500	Internal Server Error	A service error occurred

List Import Formats

Lists the set of supported import formats for annotations.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/format/import HTTP/1.1
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an AnnotationFormatListRepresentation schema XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
500	Internal Server Error	A service error occurred

Format Options

Most requests to retrieve annotations, as documented below, support a `format_option` parameter in which you can supply instructions specific to the requested export format. In general, the valid values for this parameter depends on the 'specialParameters' parameters supported by the particular Pepper Importer/Exporter module for the requested template format. The following lists the the general parameters specific to the Syntactic Annotation Service which apply to all conversions between template formats:

- `pepperImporter.corpusName=<name of the corpus>` (this option specifies the name to be used to represent the corpus being transformed)

Annotation Repository

A pre-configured annotation repository. The 1.1.0 release of the service supports remote url based repositories that follow a template pattern for retrieval of annotations according to an identifier or a specific type of annotation repository. These are the repositories from which the service can retrieve annotations.

List Annotation Repository instances

List the annotation repositories configured for this instance of the service.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/repository
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an AnnotationRepositoryListRepresentation schema XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters

404	Not Found	The requested document does not exist and/or the requested analysis returned no results
500	Internal Server Error	A service error occurred

List an Annotation Repository

List a specific annotation repository configured for this instance of the service.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/repository/{RepoId}
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Example:

```
GET /annotationservice/repository/alpheios HTTP/1.1
```

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an AnnotationRepositoryListRepresentation schema XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document does not exist and/or the requested analysis returned no results
500	Internal Server Error	A service error occurred

Text Repository

A repository from which texts/documents can be retrieved and transformed to create templates for annotation. The 1.1.0 version of the services supports both CTS repositories and repositories which can respond to URI based requests.

List Text Repository instances

List the text repositories configured for this instance of the service.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/textrepository HTTP/1.1
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an TextRepositoryListRepresentation schema XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document does not exist and/or the requested analysis returned no results
500	Internal Server Error	A service error occurred

List a specific Text Repository

List a specific text repository configured for this instance of the service.

Calling Method and Arguments

Invoked as an HTTP GET method. Send an HTTP request of the form:

```
GET /annotationservice/textrepository/{RepoId}
```

Parameter	Supported Values
Accept Header	application/xml,text/xml,application/json

Example:

```
GET /annotationservice/textrepository/xmlRepository HTTP/1.1
```

Response

On success, a response with a "202 Accepted" HTTP status code will be returned:

Parameter	Meaning
HTTP Body	An instance of an TextRepositoryListRepresentation XML document

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the Get request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document does not exist and/or the requested analysis returned no results
500	Internal Server Error	A service error occurred

Annotation

An annotation on a document, text or fragment.

Request a specific annotation or set of annotations

Calling Method and Arguments

Invoked as an HTTP GET or HTTP POST. Send an HTTP request of the form:

```
GET /annotationservice/annotation HTTP/1.1
POST /annotationservice/annotation HTTP/1.1
```

parameter	accepted values	cardinality	notes
document_id	cts urn identifying the document, document fragment or token	1	
template_format	code for the requested template format	1	
format_option	format-specific option	0..1	
repos_order	repository search order	0..1	
filter	TBD filter for limiting results to a specific annotation if multiple exist	0..*	
notify	email address or bamboo person id for notification upon completion	0..1	
wait	true or false	0..1	if not supplied, default is true (request will be submitted synchronously)
Accept Header	application/xml,text/xml,application/json		

Example:

The following request asks for all annotations on the document fragment identified as urn:cts:greekLit:tlg0085.tlg003.alpheios-text-grc1:1-100 (lines 1-100 of 'Prometheus Bound', from the 'alpheios' annotation repository):

```

POST /bsp/annotationService/annotation HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Content-Length: 131
template_format=Perseus&lang=grc&document_id=urn%3AActs%3AgreekLit%3Atlg008
5.tlg003.alpheios-text-grc1%3A1-100&repos_order=alpheios

```

Response

Synchronous requests (param wait=true)

A response with "200 (OK)" HTTP status code will be returned.

Parameter	Meaning
HTTP Body	OAC/RDF annotations as annotation body, adhering to the schema identified in the template_format request parameter.

Asynchronous requests (param wait=false)

A response with "202 (Accepted)" HTTP Status code will be returned

Parameter	Meaning
HTTP Body	A single annotation which represents a summary annotation for the request. The rdf:about value for the Annotation itself will be set to a urn representing a unique identifier for the request. The rdf:about value for the Annotation Body will be the url identifying the location the results will be stored at when complete.

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested annotations were not found or could not be retrieved.
500	Internal Server Error	A service error occurred

Parameter	Meaning
HTTP Body	XML document with AnnotationServiceError as root element containing a descriptive message.

Request an annotation or set of annotations matching certain criteria

Calling Method and Arguments

Invoked as an HTTP GET or HTTP POST. Send an HTTP request of the form:

```
GET /annotation/service/annotation/match HTTP/1.1
POST /annotation/service/annotation/match HTTP/1.1
```

parameter	accepted values	cardinality	notes
document_id	cts urn identifying the document, document fragment or token	0..1	
lang	language of interest	0..1	
template_format	code for the requested template format	1	
format_option	format-specific option	0..1	
repos_order	repository search order	0..1	
filterBy	filter field for match	1	(valid query options for each repository are available in the repository list output)
filterOp	filter operation for match	1	(currently only supported value is 'equals')
filterValue	filter field value match	1	
notify	email address or bamboo person id for notification upon completion	0..1	
wait	true or false	0..1	if not supplied, default is true (request will be submitted synchronously)
Accept Header	application/xml,text/xml,application/json		

Example:

The following request asks for annotations on the document fragment identified as urn:cts:greekLit:tlg0085.tlg003.alpheios-text-grc1:1-100 (lines 1-100 of 'Prometheus Bound', in the 'alpheios' annotation repository, where the word's part of speech matches 'noun':

```
POST /annotation/service/annotation/match HTTP/1.1
Accept: application/json
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Content-Length: 177
template_format=Perseus&lang=grc&document_id=urn%3Acts%3AgreekLit%3Atlg0085.tlg003.alpheios-text-grc1%3A1-100&repos_order=alpheios&filterOp=equals&filterValue=noun&filterBy=pos
```

Response

Synchronous requests (param wait=true)

A response with "200 (OK)" HTTP status code will be returned.

Parameter	Meaning
HTTP Body	OAC/RDF annotations as annotation body, adhering to the schema identified in the template_format request parameter.

Asynchronous requests (param wait=false)

A response with "202 (Accepted)" HTTP Status code will be returned

Parameter	Meaning
HTTP Body	A single annotation which represents a summary annotation for the request. The rdf:about value for the Annotation itself will be set to a urn representing a unique identifier for the request. The rdf:about value for the Annotation Body will be the url identifying the location the results will be stored at when complete.

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document was not found or could not be retrieved.
500	Internal Server Error	A service error occurred

Parameter	Meaning
HTTP Body	XML document with AnnotationServiceError as root element containing a descriptive message.

Annotation Template (Document)

An annotation template for a specified document.

Create an annotation template for a specific document.

Calling Method and Arguments

Invoked as an HTTP GET or HTTP POST. Send an HTTP request of the form:

```
GET /annotationService/annotation/template/document HTTP/1.1
POST /annotationService/annotation/template/document HTTP/1.1
```

parameter	accepted values	cardinality	notes
document_id	document (or document fragment) id (cts urn, cmis object id)	1	
repos_type	repository type (e.g. cts, xml)	0..1	
repos_uri	base uri for the repository	0..1	
lang	languages of interest in the document	1..*	
template_format	code for the requested template format	1	
format_option	format-specific option	0..1	
notify	email address or bamboo person id for notification upon completion	0..1	
wait	true or false	0..1	if not supplied, default is true (request will be submitted synchronously)

Accept Header	application/xml,text/xml,application/json	
---------------	---	--

Example:

```
POST /bsp/annotationservice/annotation/template/document HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Content-Length: 164
template_format=Perseus&lang=lat&document_id=urn%3Acts%3AlatinLit%3Asto0179.stoa001.stoa001%3A1.1.1&repos_type=cts&repos_uri=http%3A%2F%2Fhc.latin.ppspot.com%2FCTS
```

Response

Synchronous requests (param wait=true)

A response with "200 (OK)" HTTP status code will be returned.

Parameter	Meaning
HTTP Body	One or more OAC/RDF Annotation templates for requested text

Asynchronous requests (param wait=false)

A response with "202 (Accepted)" HTTP Status code will be returned

Parameter	Meaning
HTTP Body	A single annotation which represents a summary annotation for the request. The rdf:about value for the Annotation itself will be set to a urn representing a unique identifier for the request. The rdf:about value for the Annotation Body will be the url identifying the location the results will be stored at when complete.

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document was not found or could not be retrieved.
500	Internal Server Error	A service error occurred

Parameter	Meaning
HTTP Body	XML document with AnnotationServiceError as root element containing a descriptive message.

Annotation Template (Text)

An annotation template for supplied text.

Create an annotation template for supplied text

Calling Method and Arguments

Invoked as an HTTP GET or HTTP POST. Send an HTTP request of the form:

```
GET /annotation-service/annotation/template/text HTTP/1.1
POST /annotation-service/annotation/template/text HTTP/1.1
```

parameter	accepted values	cardinality	notes
text	the supplied text	0..1	
text_uri	a uri for the supplied text	0..1	If both text and text_uri are supplied, the uri will be used as the identifier for the text only
template_format	code for the requested template format	1	
mime_type	mime-type of the supplied text (text/html, text/xml, or text/plain)	1	
format_option	format-specific option	0..1	
lang	languages of interest in the supplied text	1..*	
notify	email address or bamboo person id for notification upon completion	0..1	
wait	true or false	0..1	if not supplied, default is true (request will be submitted synchronously)
Accept Header	application/xml,text/xml,application/javascript		

Example:

```
POST /annotation-service/annotation/template/text HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Content-Length: 79
text=veni%20vidi%20vici&template_format=Perseus&lang=lat&mime_type=text%2Fplain
```

Response

Synchronous requests (param wait=true)

A response with "200 (OK)" HTTP status code will be returned.

Parameter	Meaning
HTTP Body	One or more OAC/RDF Annotation templates for requested text

Asynchronous requests (param wait=false)

A response with "202 (Accepted)" HTTP Status code will be returned

Parameter	Meaning
-----------	---------

HTTP Body	A single annotation which represents a summary annotation for the request. The rdf:about value for the Annotation itself will be set to a urn representing a unique identifier for the request. The rdf:about value for the Annotation Body will be the url identifying the location the results will be stored at when complete.
-----------	---

Exceptions

If an error occurred, some non-2xx code will be returned. Check the [HTTP Status Code](#) that is returned in the response's HTTP headers for the specific error. The following errors may be returned in response to the request:

Error (Status Code)	Meaning	Returned When
400	Bad Request	Request is missing required parameters
404	Not Found	The requested document was not found or could not be retrieved.
500	Internal Server Error	A service error occurred

Parameter	Meaning
HTTP Body	XML document with AnnotationServiceError as root element containing a descriptive message.

SOA Layer API

Javadoc will be linked once it is generated and published.

See [Javadoc](#).

Notifications

If the notify parameter has been supplied and set to an email address an email will be sent to that address upon completion of the request. If the notify parameter is set to a bamboo person id, notifications will be sent according to user preferences. The body of the notification messages will contain the unique identifier for the request (as returned in the rdf:about value for the annotation returned by the requested), the current status, and the location at which the results can be retrieved.

Tests

See [Tests](#)